



BC-L



14,000 to 24,000 lb Capacity

INDUSTRIAL BURDEN CARRIER



TROWIN INDUSTRIES, INC.

737 Herbert St. | Chippewa Falls, WI 54729

715-738-1690 PH | 715-738-1693 FX

www.trowin.com

specifications



BC-L

14,000 to 24,000 lbs Capacity Industrial Burden Carrier



Engine: Cummins B4.5 ltr. 4-cylinder Diesel Engine, 80 hp(Tier 3 Compliant)
Zenith 4.4 ltr. 6-cylinder EFI Gasoline Engine w/ shutdown system (Tier 3 Compliant)

Transmission: Ford (Certified) C-6 Automatic Transmission, 2 or 3 Speeds Forward & 1 Reverse (w/ Cummins or I-6 ns)

Drive Axle: Heavy Duty Automotive Type, Leaf Spring Mounted

Steer Axle: Heavy Duty Industrial Beam, Leaf Spring Mounted

Brakes: Service; 4-Wheel Split System, Power Assisted Disc Brakes Parking; Lever Operated on Transmission Output

Steering: Full-Time Power Assisted, Hydrostatic System

Electrical System: 12-Volt Negative Ground, 95 Amp Alternator, Keyed Anti-Restart Ignition, Horn, Sealed Beam Headlights (2), Sealed Beam Stop/Tail Lights (2)

Instrumentation: Gauges: Engine Hour Meter, Water Temperature, Fuel Level Warning Lights: Engine Temperature, Low Oil Pressure, Transmission Temperature, Voltage, Brake System Failure, Parking Brake Engaged

Tires: 265/70R19 Pneumatic, Single Front: 255/70R22.5 Dual Rear

Seat: Single Operator Polyurethane Foam Seat; For & Aft Adjuster

Frame: Laser Cut, Unitized All Welded Heavy Duty Construction, 8x3 Tubing Frame Rails, 3/8" Body Components, Media Blasted for Superior Finish Adhesion

Finish: Primer: 2-part Grey Epoxy Primer Finish: 2-part Polyurethane (White, Yellow or Orange)(std)

Options: LPG, CNG, Diesel, Electric, Overhead Guard, Cab, Heater/Defroster, Back-up Alarm, Turn Signals, Tilt Steering, Suspension Seat, Couplers, Other Options Available Please Consult Dealer or Factory

Model #	BCL-140	BCL-160	BCL-180	BCL-200	BCL-220	BCL-240
Capacity(lbs)	14,000	16,000	18,000	20,000	22,000	24,000



specifications subject to change without notice

Last Update 1/1/08